

SAFETY DATA SHEET



Valvoline™ HEAVY DUTY BRAKE PARTS CLEANER

Version	Revision Date:	SDS Number:	Date of last issue: 05/18/2018
3.0	09/06/2018	600000000515	Date of first issue: 05/23/2016

SECTION 1. IDENTIFICATION

Product name : VAL NON-CHLR LOW VOC BPC 12/15 OC

Product code : 602371

Manufacturer or supplier's details

Company name of supplier : Niteo Products, LLC

Address : Dallas TX 75225

Email Address : EHS@niteoproducts.com

Telephone : 1-844-696-4836

Emergency telephone number : 1-800-424-9300 / 1-703-741-5970

Recommended use of the chemical and restrictions on use

Recommended use : CLEANER

Restrictions on use : Use only outdoors or in a well-ventilated area.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Flammable aerosols : Category 1

Acute toxicity (Oral) : Category 4

Acute toxicity (Inhalation) : Category 4

Acute toxicity (Dermal) : Category 4

Skin irritation : Category 2

Eye irritation : Category 2A

Specific target organ toxicity - single exposure : Category 1 (Central nervous system, Eyes)

Specific target organ toxicity - single exposure : Category 3 (Respiratory system, Central nervous system)

Specific target organ toxicity - repeated exposure : Category 2 (Auditory system)

SAFETY DATA SHEET



Valvoline™ HEAVY DUTY BRAKE PARTS CLEANER

Version	Revision Date:	SDS Number:	Date of last issue: 05/18/2018
3.0	09/06/2018	600000000515	Date of first issue: 05/23/2016

Aspiration hazard : Category 1

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : Extremely flammable aerosol.
Harmful if swallowed, in contact with skin or if inhaled.
May be fatal if swallowed and enters airways.
Causes skin irritation.
Causes serious eye irritation.
May cause respiratory irritation.
May cause drowsiness or dizziness.
Causes damage to organs (Central nervous system, Eyes).
May cause damage to organs (Auditory system) through prolonged or repeated exposure.

Precautionary statements : **Prevention:**
Keep away from heat/sparks/open flames/hot surfaces. No smoking.
Do not spray on an open flame or other ignition source.
Pressurized container: Do not pierce or burn, even after use.
Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
Wash skin thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

IF SWALLOWED: Immediately call a POISON CENTER/doctor.
IF ON SKIN: Wash with plenty of water. Call a POISON CENTER/doctor if you feel unwell.
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF exposed: Call a POISON CENTER or doctor/ physician.
Do NOT induce vomiting.
If skin irritation occurs: Get medical advice/ attention.
If eye irritation persists: Get medical advice/ attention.
Take off contaminated clothing and wash before reuse.

Storage:

Store in a well-ventilated place. Keep container tightly closed.
Store locked up.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

**Valvoline™ HEAVY DUTY BRAKE PARTS
CLEANER**

Version	Revision Date:	SDS Number:	Date of last issue: 05/18/2018
3.0	09/06/2018	600000000515	Date of first issue: 05/23/2016

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Acetone	67-64-1	>= 50 - < 70
Methanol	67-56-1	>= 20 - < 30
Xylene	1330-20-7	>= 20 - < 30
Ethylbenzene	100-41-4	>= 5 - < 10
Carbon dioxide	124-38-9	>= 5 - < 10

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.
- If inhaled : Move to fresh air.
IF INHALED: Call a POISON CENTER/ doctor if you feel unwell.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : If on clothes, remove clothes.
Call a physician or poison control centre immediately.
Remove contaminated clothing. If irritation develops, get medical attention.
If on skin, rinse well with water.
Wash contaminated clothing before re-use.
If skin irritation persists, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Obtain medical attention.
Do NOT induce vomiting.
Rinse mouth with water.

SAFETY DATA SHEET



Valvoline™ HEAVY DUTY BRAKE PARTS CLEANER

Version	Revision Date:	SDS Number:	Date of last issue: 05/18/2018
3.0	09/06/2018	600000000515	Date of first issue: 05/23/2016

Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed :

- Harmful if swallowed, in contact with skin or if inhaled.
- May be fatal if swallowed and enters airways.
- Causes skin irritation.
- Causes serious eye irritation.
- May cause respiratory irritation.
- May cause drowsiness or dizziness.
- Causes damage to organs.
- May cause damage to organs through prolonged or repeated exposure.
- Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material.
- This product contains methanol which can cause intoxication and central nervous system depression. Methanol is metabolized to formic acid and formaldehyde. These metabolites can cause metabolic acidosis, visual disturbances and blindness. Since metabolism is required for these toxic symptoms, their onset may be delayed from 6 to 30 hours following ingestion. Ethanol competes for the same metabolic pathway and has been used to prevent methanol metabolism. Ethanol administration is indicated in symptomatic patients or at blood methanol concentrations above 20 ug/dl. Methanol is effectively removed by hemodialysis.
- This material (or a component) has produced hyperglycemia and ketosis following substantial ingestion.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media :

- Water spray
- Carbon dioxide (CO₂)
- Dry chemical
- Alcohol-resistant foam

Unsuitable extinguishing media :

- High volume water jet

Specific hazards during fire-fighting :

- Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products :

- Carbon oxides

Specific extinguishing methods :

- Product is compatible with standard fire-fighting agents.

Further information :

- Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Fire residues and contaminated fire extinguishing water must

**Valvoline™ HEAVY DUTY BRAKE PARTS
CLEANER**

Version	Revision Date:	SDS Number:	Date of last issue: 05/18/2018
3.0	09/06/2018	600000000515	Date of first issue: 05/23/2016

be disposed of in accordance with local regulations.
Use a water spray to cool fully closed containers.

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.
for firefighters

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Remove all sources of ignition.
Ensure adequate ventilation.
Avoid breathing dust.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Evacuate personnel to safe areas.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions : Prevent further leakage or spillage if safe to do so.
Prevent product from entering drains.
Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
Keep away from open flames, hot surfaces and sources of ignition.
Use only explosion-proof equipment.
Do not spray on a naked flame or any incandescent material.

Advice on safe handling : Open drum carefully as content may be under pressure.
Provide sufficient air exchange and/or exhaust in work rooms.
Do not breathe vapours/dust.
Do not smoke.
Take precautionary measures against static discharges.
Avoid contact with skin and eyes.
Dispose of rinse water in accordance with local and national regulations.
Container hazardous when empty.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and

SAFETY DATA SHEET


**Valvoline™ HEAVY DUTY BRAKE PARTS
CLEANER**

Version 3.0 Revision Date: 09/06/2018 SDS Number: 600000000515 Date of last issue: 05/18/2018
Date of first issue: 05/23/2016

kept upright to prevent leakage.
Observe label precautions.
No smoking.

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Acetone	67-64-1	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	250 ppm 590 mg/m3	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m3	OSHA Z-1
		TWA	750 ppm 1,800 mg/m3	OSHA P0
		STEL	1,000 ppm 2,400 mg/m3	OSHA P0
Methanol	67-56-1	TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH
		TWA	200 ppm 260 mg/m3	NIOSH REL
		ST	250 ppm 325 mg/m3	NIOSH REL
		TWA	200 ppm 260 mg/m3	OSHA Z-1
		STEL	250 ppm 325 mg/m3	OSHA P0
		TWA	200 ppm 260 mg/m3	OSHA P0
Ethylbenzene	100-41-4	TWA	20 ppm	ACGIH
		TWA	100 ppm 435 mg/m3	NIOSH REL
		ST	125 ppm 545 mg/m3	NIOSH REL
		TWA	100 ppm 435 mg/m3	OSHA Z-1
		TWA	100 ppm 435 mg/m3	OSHA P0
		STEL	125 ppm 545 mg/m3	OSHA P0
Carbon dioxide	124-38-9	TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm 9,000 mg/m3	NIOSH REL
		ST	30,000 ppm 54,000 mg/m3	NIOSH REL

SAFETY DATA SHEET


**Valvoline™ HEAVY DUTY BRAKE PARTS
CLEANER**

Version 3.0 Revision Date: 09/06/2018 SDS Number: 600000000515 Date of last issue: 05/18/2018
Date of first issue: 05/23/2016

		TWA	5,000 ppm 9,000 mg/m ³	OSHA Z-1
		TWA	10,000 ppm 18,000 mg/m ³	OSHA P0
		STEL	30,000 ppm 54,000 mg/m ³	OSHA P0

Hazardous components without workplace control parameters

Components	CAS-No.
Xylene	1330-20-7

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
Acetone	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI
Methanol	67-56-1	Methanol	Urine	End of shift (As soon as possible after exposure ceases)	15 mg/l	ACGIH BEI
Ethylbenzene	100-41-4	Sum of mandelic acid and phenyl gly-oxalic acid	Urine	End of shift (As soon as possible after exposure ceases)	0.15 g/g creatinine	ACGIH BEI

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.
In the case of dust or aerosol formation use respirator with an approved filter.

Hand protection

Remarks : Wear resistant gloves (consult your safety equipment supplier). The suitability for a specific workplace should be discussed with the producers of the protective gloves. Discard gloves that show tears, pinholes, or signs of wear.

SAFETY DATA SHEET



Valvoline™ HEAVY DUTY BRAKE PARTS CLEANER

Version	Revision Date:	SDS Number:	Date of last issue: 05/18/2018
3.0	09/06/2018	600000000515	Date of first issue: 05/23/2016

- | | | |
|--------------------------|---|---|
| Eye protection | : | Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist. |
| Skin and body protection | : | Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Wear as appropriate:
Impervious clothing
Flame-resistant clothing
Safety shoes |
| Hygiene measures | : | Handle in accordance with good industrial hygiene and safety practice.
When using do not smoke.
When using do not eat or drink. |

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- | | | |
|--|---|---|
| Appearance | : | aerosol |
| Odour | : | No data available |
| pH | : | No data available |
| Melting point/freezing point | : | No data available |
| Boiling point/boiling range | : | 56 °C
(1,013 hPa)
The value is calculated |
| Flash point | : | -20 °C |
| Evaporation rate | : | No data available |
| Flammability (solid, gas) | : | No data available |
| Self-ignition | : | No data available |
| Upper explosion limit / Upper flammability limit | : | 36 %(V)
The value is calculated |
| Lower explosion limit / Lower flammability limit | : | 1 %(V)
The value is calculated |
| Vapour pressure | : | 307.9 hPa (25 °C)
The value is calculated |
| Density | : | 0.8132 g/cm ³ (15.56 °C) |
| Solubility(ies)
Water solubility | : | No data available |
| Partition coefficient: n-octanol/water | : | No data available |

SAFETY DATA SHEET



Valvoline™ HEAVY DUTY BRAKE PARTS CLEANER

Version	Revision Date:	SDS Number:	Date of last issue: 05/18/2018
3.0	09/06/2018	600000000515	Date of first issue: 05/23/2016

Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	No data available
Oxidizing properties	:	No data available
Heat of combustion	:	estimated 30.0 kJ/g
VOC % By Weight	:	42.6 %

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Acids Bases Aluminium Amines Ammonia halogens Lead Peroxides Reducing agents Strong bases Strong oxidizing agents Zinc
Hazardous decomposition products	:	Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Eye contact
Skin contact
Ingestion

Acute toxicity

Harmful if swallowed, in contact with skin or if inhaled.

Product:

Acute oral toxicity	:	Acute toxicity estimate: 433.88 mg/kg Method: Calculation method
Acute inhalation toxicity	:	Acute toxicity estimate: 1.62 mg/l

**Valvoline™ HEAVY DUTY BRAKE PARTS
CLEANER**

Version	Revision Date:	SDS Number:	Date of last issue: 05/18/2018
3.0	09/06/2018	600000000515	Date of first issue: 05/23/2016

Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: 1,171 mg/kg
Method: Calculation method

Components:**Acetone:**

Acute oral toxicity : LD50 (Rat, female): 5,800 mg/kg

Acute inhalation toxicity : LC50 (Rat, female): 76 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 7,426 mg/kg

Methanol:

Acute oral toxicity : LDLo (Humans): 300 mg/kg
Assessment: The component/mixture is toxic after single ingestion.

Acute inhalation toxicity : Test atmosphere: dust/mist
Assessment: The component/mixture is toxic after short term inhalation.

Acute dermal toxicity : LD50 (Rabbit): 12,800 mg/kg
Assessment: The component/mixture is toxic after single contact with skin.

Xylene:

Acute oral toxicity : LD50 (Rat): 3,523 - 8,600 mg/kg

Acute inhalation toxicity : LC50 (Rat): 6700 ppm
Exposure time: 4 h
Test atmosphere: vapour

Assessment: The component/mixture is moderately toxic after short term inhalation.

Acute dermal toxicity : LD50 (Rabbit): 1,700 mg/kg

Ethylbenzene:

Acute oral toxicity : LD50 (Rat): ca. 3,500 mg/kg

Acute inhalation toxicity : LC50 (Rat): 4000 ppm
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 17,800 mg/kg

Valvoline™ HEAVY DUTY BRAKE PARTS CLEANER

Version	Revision Date:	SDS Number:	Date of last issue: 05/18/2018
3.0	09/06/2018	600000000515	Date of first issue: 05/23/2016

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks: May cause skin irritation and/or dermatitis.

Components:

Acetone:

Result: Possibly irritating to skin

Result: Repeated exposure may cause skin dryness or cracking.

Methanol:

Species: Rabbit

Result: No skin irritation

Xylene:

Assessment: Irritating to skin.

Result: Irritating to skin.

Ethylbenzene:

Result: Irritating to skin.

Carbon dioxide:

Assessment: No skin irritation

Result: No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:

Acetone:

Result: Irritating to eyes.

Assessment: Irritating to eyes.

Methanol:

Species: Rabbit

Result: Possibly irritating to eyes

Xylene:

Result: Irritating to eyes.

**Valvoline™ HEAVY DUTY BRAKE PARTS
CLEANER**

Version	Revision Date:	SDS Number:	Date of last issue: 05/18/2018
3.0	09/06/2018	600000000515	Date of first issue: 05/23/2016

Ethylbenzene:

Result: Irritating to eyes.

Carbon dioxide:

Result: No eye irritation

Respiratory or skin sensitisation**Skin sensitisation**

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:**Methanol:**

Test Type: Maximisation Test

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

Method: OECD Test Guideline 406

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Components:**Ethylbenzene:**

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

IARC

Group 2B: Possibly carcinogenic to humans

Ethylbenzene

100-41-4

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause respiratory irritation.

May cause drowsiness or dizziness.

Causes damage to organs (Central nervous system, Eyes).

**Valvoline™ HEAVY DUTY BRAKE PARTS
CLEANER**

Version	Revision Date:	SDS Number:	Date of last issue: 05/18/2018
3.0	09/06/2018	600000000515	Date of first issue: 05/23/2016

Components:**Acetone:**

Exposure routes: Inhalation
Target Organs: Nervous system
Assessment: May cause drowsiness or dizziness.

Methanol:

Target Organs: Central nervous system, Eyes
Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 1.

Xylene:

Assessment: May cause drowsiness or dizziness., May cause respiratory irritation.

STOT - repeated exposure

May cause damage to organs (Auditory system) through prolonged or repeated exposure.

Components:**Ethylbenzene:**

Target Organs: Auditory system
Assessment: May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Components:**Acetone:**

May be harmful if swallowed and enters airways.

Xylene:

May be fatal if swallowed and enters airways.

Ethylbenzene:

May be fatal if swallowed and enters airways.

Further information**Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

SECTION 12. ECOLOGICAL INFORMATION

SAFETY DATA SHEET



Valvoline™ HEAVY DUTY BRAKE PARTS CLEANER

Version	Revision Date:	SDS Number:	Date of last issue: 05/18/2018
3.0	09/06/2018	600000000515	Date of first issue: 05/23/2016

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues	:	Dispose of in accordance with all applicable local, state and federal regulations.
Contaminated packaging	:	Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

International Regulations

IATA-DGR

Not permitted for transport

IMDG-Code

UN number	:	UN 1950
Proper shipping name	:	Aerosols
Class	:	2.1
Subsidiary risk	:	6.1
Packing group	:	Not assigned by regulation
Labels	:	2.1 (6.1)
EmS Code	:	F-D, S-U
Marine pollutant	:	no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

UN/ID/NA number	:	UN 1950
Proper shipping name	:	Aerosols
Class	:	2.1
Packing group	:	Not assigned by regulation
Labels	:	2.1
ERG Code	:	126
Marine pollutant	:	no

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

SAFETY DATA SHEET



Valvoline™ HEAVY DUTY BRAKE PARTS CLEANER

Version 3.0 Revision Date: 09/06/2018 SDS Number: 600000000515 Date of last issue: 05/18/2018
Date of first issue: 05/23/2016

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Xylene	1330-20-7	100	496
Xylene	1330-20-7	100	100 (F003)

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Acute toxicity (any route of exposure)
Skin corrosion or irritation
Serious eye damage or eye irritation
Specific target organ toxicity (single or repeated exposure)
Aspiration hazard

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

Methanol	67-56-1	>= 20 - < 30 %
Ethylbenzene	100-41-4	>= 5 - < 10 %

California Prop. 65

WARNING: This product can expose you to chemicals including Ethylbenzene, Benzene, which is/are known to the State of California to cause cancer, and Methanol, Toluene, Benzene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SAFETY DATA SHEET




Valvoline™ HEAVY DUTY BRAKE PARTS CLEANER

Version	Revision Date:	SDS Number:	Date of last issue: 05/18/2018
3.0	09/06/2018	6000000000515	Date of first issue: 05/23/2016

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Special hazard.

Revision Date : 09/06/2018

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN